

## CLAIMS

What is claimed is:

1. A fuel-concentration indicator incorporated in a fuel cell that operates by oxidizing a fuel solution, the fuel-concentration indicator comprising:
  - a volume of fuel solution; and
  - a float responsive to fuel solution density immersed in the volume of fuel solution.
2. The fuel-concentration indicator of claim 1 wherein the volume of the fuel solution is contained within an anode reservoir.
3. The fuel-concentration indicator of claim 1 wherein the volume of the fuel solution is contained within a float chamber in fluid contact with the anode reservoir and separated from the anode reservoir by a semi-permeable filter membrane.
4. The fuel-concentration indicator of claim 1 wherein the volume of the fuel solution is contained within a float chamber in fluid contact with the anode reservoir and separated from the anode reservoir by a fuel channel.
5. The fuel-concentration indicator of claim 4 further including a semi-permeable membrane between the fuel solution in the anode reservoir and the fuel solution in the float chamber.
6. The fuel-concentration indicator of claim 1 further comprising a fuel scale aligned with a transparent window on an exterior surface of the fuel cell in fluid communication with the volume of fuel solution.
7. The fuel-concentration indicator of claim 1 wherein the float contains a fuel indicator bar.

20140808 04103

8. The fuel-concentration indicator of claim 1 wherein the float controls release of the fuel solution.

9. The fuel concentration indicator of claim 8 wherein the float completes an electrical circuit controlling the release of the fuel solution.

10. A method for determining the concentration of fuel in a fuel solution in a fuel cell having an anode reservoir, the method comprising:

adding a float to the fuel solution; and

determining the concentration of fuel in the fuel solution by comparing the position of the float to numeric values contained on a fuel scale.

11. The method of claim 10 wherein determination of the concentration of fuel in the fuel solution is determined by viewing the position of the float through a transparent window.

12. The method of claim 10 wherein determination of the concentration of fuel in the fuel solution is determined by viewing the position of the float through a transparent window of a float chamber, the float chamber in fluid contact with the anode reservoir and separated from the anode reservoir by a semi-permeable membrane.

13. The method of claim 10 wherein determination of the concentration of fuel in the fuel solution is determined by viewing the position of the float through a transparent window of a float chamber, the float chamber in fluid contact with the anode reservoir and separated from the anode reservoir by a fuel channel.

14. The method of claim 13 further including a semi-permeable membrane between the fuel solution in the anode reservoir and fuel solution in the float chamber.

15. A fuel-concentration indicator incorporated in a fuel cell that operates by oxidizing a fuel solution, the fuel-concentration indicator comprising:

a volume of fuel solution; and

a density-indicator means responsive to fuel solution density within the volume of fuel solution.

16. The fuel-concentration indicator of claim 15 further including a quantifying means by which the position of the density-indicator means can be translated to a numeric representation of the fuel concentration in the fuel solution.

20170830 04:40:33